



# MT15N011A

## 主要参数 MAIN CHARACTERISTICS

$I_D$	110A
$V_{DSS}$	150V
$R_{dson-max}$ (@ $V_{gs}=10V$ )	13m $\Omega$
$Q_g-typ$	130.26nC

### 用途

- 电信与工业领域隔离 DC/DC 转换
- 同步整流领域
- 汽车应用
- 不间断电源

### 产品特性

- 低栅极电荷
- 低  $R_{dson}$
- 开关速度快
- 产品全部经过雪崩测试
- 高抗  $dv/dt$  能力
- RoHS 产品



### APPLICATIONS

- Isolated DC/DC Converters in Telecom and Industrial
- Synchronous Rectification
- Automotive
- UPS

### FEATURES

- Low gate charge
- Low  $R_{dson}$
- Fast switching
- 100% avalanche tested
- Improved  $dv/dt$  capability
- RoHS product

## 封装 Package



## 订货信息 ORDER MESSAGE

订货型号 Order codes				印 记 Marking	封 装 Package
有卤-条管 Halogen-Tube	无卤-条管 Halogen-Free-Tube	有卤-编带 Halogen-Reel	无卤-编带 Halogen-Free-Reel		
MT15N011A-CG-B	MT15N011A-CG-BR	N/A	N/A	MT15N011A	TO-220C-Y1



## 绝对最大额定值 ABSOLUTE RATINGS (Tc=25℃)

项 目 Parameter	符 号 Symbol	数 值 Value	单 位 Unit
		MT15N011A	
最高漏极-源极直流电压 Drain-Source Voltage	V <sub>DSS</sub>	150	V
连续漏极电流 Drain Current -continuous	I <sub>D</sub> T=25℃	110*	A
	I <sub>D</sub> T=100℃	81*	A
最大脉冲漏极电流 (注1) Drain Current - pulse (note 1)	I <sub>DM</sub>	440*	A
最高栅源电压 Gate-Source Voltage	V <sub>GSS</sub>	+20/-20V	V
单脉冲雪崩能量 (注2) Single Pulsed Avalanche Energy (note 2)	E <sub>AS</sub>	1000	mJ
雪崩电流 (注1) Avalanche Current (note 1)	I <sub>AS</sub>	63	A
耗散功率 Power Dissipation	P <sub>D</sub> T <sub>C</sub> =25℃ -Derate above 25℃	312.5	W
		2.5	W/℃
最高结温及存储温度 Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55~+150	℃
引线最高焊接温度 Maximum Lead Temperature for Soldering Purposes	T <sub>L</sub>	300	℃

\*漏极电流由最高结温限制

\*Drain current limited by maximum junction temperature



## 电特性 ELECTRICAL CHARACTERISTICS

项 目 Parameter	符 号 Symbol	测试条件 Tests conditions	最小 Min	典型 Typ	最大 Max	单 位 Units
<b>关态特性 Off –Characteristics</b>						
漏—源击穿电压 Drain-Source Voltage	$BV_{DSS}$	$I_D=250\mu A, V_{GS}=0V$	150	-	-	V
零栅压下漏极漏电流 Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=150V, V_{GS}=0V,$ $T_C=25^\circ C$	-	-	1	$\mu A$
		$V_{DS}=150V, V_{GS}=0V,$ $T_C=100^\circ C$	-	-	250	$\mu A$
正向栅极体漏电流 Gate-body leakage current, forward	$I_{GSSF}$	$V_{DS}=0V, V_{GS}=20V$	-	-	100	nA
反向栅极体漏电流 Gate-body leakage current, reverse	$I_{GSSR}$	$V_{DS}=0V, V_{GS}=-20V$	-	-	-100	nA
<b>通态特性 On-Characteristics</b>						
阈值电压 Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D=250\mu A$	3		5	V
静态导通电阻 Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = 10V, I_D=62A$	-	10.7	13	m $\Omega$
<b>动态特性 Dynamic Characteristics</b>						
输入电容 Input capacitance	$C_{iss}$	$V_{DS}=50V,$ $V_{GS}=0V,$ $f=1.0MHz$	-	5740	-	pF
输出电容 Output capacitance	$C_{oss}$		-	309	-	pF
反向传输电容 Reverse transfer capacitance	$C_{rss}$		-	180	-	pF

**电特性 ELECTRICAL CHARACTERISTICS****开关特性 Switching Characteristics**

延迟时间 Turn-On delay time	$t_{d(on)}$	$V_{DD}=98V, I_D=62A, R_G=2.2\Omega$	-	27.2	-	ns
上升时间 Turn-On rise time	$t_r$		-	96.2	-	ns
延迟时间 Turn-Off delay time	$t_{d(off)}$	$V_{GS}=10V$ (note 3, 4)	-	48.8	-	ns
下降时间 Turn-Off Fall time	$t_f$		-	39.6	-	ns
栅极电荷总量 Total Gate Charge	$Q_g$	$V_{DS}=75V,$ $I_D=62A$ $V_{GS}=10V$ (note 3, 4)	-	130.2	-	nC
栅-源电荷 Gate-Source charge	$Q_{gs}$		-	46.68	-	nC
栅-漏电荷 Gate-Drain charge	$Q_{gd}$		-	54.18	-	nC

**漏-源二极管特性及最大额定值 Drain-Source Diode Characteristics and Maximum Ratings**

正向压降 Drain-Source Diode Forward Voltage	$V_{SD}$	$T_J=25^\circ C, V_{GS}=0V, I_S=62A$	-	-	1.3	V
正向连续电流 Diode continuous forward current	$I_S$	$V_G=V_D=0V, \text{force current}$			110	A
正向脉冲电流 Diode pulse current	$I_{SM}$				440	A
反向恢复时间 Reverse recovery time	$T_{rr}$	$T_J=25^\circ C, I_F=62A, V_{DD}=130V,$ $dI_F/dt=100A/\mu A(\text{note 3})$	-	81.8	-	ns
反向恢复电荷 Reverse recovery charge	$Q_{rr}$		-	311.1	-	nC

**热特性 THERMAL CHARACTERISTIC**

项 目 Parameter	符 号 Symbol	最大 Max	单 位 Unit
		MT20N024	
结到管壳的热阻 Thermal Resistance, Junction to Case	$R_{th(j-c)}$	0.4	$^\circ C/W$
结到环境的热阻 Thermal Resistance, Junction to Ambient	$R_{th(j-A)}$	60	$^\circ C/W$

注释:

- 1: 脉冲宽度由最高结温限制
- 2:  $V_{DD}=50V, L=0.5mH, R_G=25\Omega, I_{AS}=70A$  起始结温  $T_J=25^\circ C$
- 3: 脉冲测试: 脉冲宽度 $\leq 400\mu s$ , 占空比 $\leq 2\%$
- 4: 基本与工作温度无关


Notes:

- 1: Pulse width limited by maximum junction temperature
- 2:  $V_{DD}=50V, L=0.5mH, R_G=25\Omega, I_{AS}=70A$  Starting  $T_J=25^\circ C$
- 3: Pulse Test: Pulse Width  $\leq 400\mu s$ , Duty Cycle  $\leq 2\%$
- 4: Essentially independent of operating temperature




特征曲线 ELECTRICAL CHARACTERISTICS (curves)


On-Region Characteristics




Transfer Characteristics




On-Resistance Variation vs. Drain Current and Gate Voltage




Body Diode Forward Voltage Variation vs. Source Current



Capacitance Characteristics




Gate Charge Characteristics






特征曲线 ELECTRICAL CHARACTERISTICS (curves)


Breakdown Voltage Variation vs. Temperature




On-Resistance Variation vs. Temperature



Maximum Safe Operation Area




Transient Thermal Response Curve





TO-220C-Y1

单位 Unit: mm



符号 symbol	MIN	NOM	MAX
*A	4.47	4.57	4.67
*A1	1.25	1.30	1.40
*A2	2.30	2.40	2.50
*b	0.70	0.80	0.90
*b2	1.12	1.27	1.42
*c	0.45	0.50	0.60
*D	15.50	15.70	15.90
*D1	8.90	9.10	9.30
D2	6.30BSC		
*E	9.80	10.00	10.20
E1	7.80BSC		
e	2.54 BSC		
*e1	5.08 BSC		
*H	6.40	6.60	6.80
*L	13.30	13.50	13.70
*L1	2.90	3.10	3.30
* $\Phi_p$	3.45	3.60	3.75
Q	2.70	2.80	2.90
$\theta$	1°	3°	5°



### 注意事项

1. 吉林华微电子股份有限公司的产品销售分为直销和销售代理，无论哪种方式，订货时请与公司核实。
2. 购买时请认清公司商标，如有疑问请与公司本部联系。
3. 在电路设计时请不要超过器件的绝对最大额定值，否则会影响整机的可靠性。
4. 本说明书如有版本变更不另外告知。

### NOTE

1. Jilin Sino-microelectronics co., Ltd sales its product either through direct sales or sales agent , thus, for customers, when ordering , please check with our company.
2. We strongly recommend customers check carefully on the trademark when buying our product, if there is any question, please don't be hesitate to contact us.
3. Please do not exceed the absolute maximum ratings of the device when circuit designing.
4. Jilin Sino-microelectronics co., Ltd reserves the right to make changes in this. specification sheet and is subject to change without prior notice.

### 联系方式

#### 吉林华微电子股份有限公司

公司地址：吉林省吉林市深圳街 99 号

邮编：132013

总机：86-432-64678411

传真：86-432-64665812

网址：[www.hwdz.com.cn](http://www.hwdz.com.cn)

### CONTACT

#### JILIN SINO-MICROELECTRONICS CO., LTD.

ADD: No.99 Shenzhen Street, Jilin City, Jilin Province, China.

Post Code: 132013

Tel: 86-432-64678411

Fax: 86-432-64665812

Web Site: [www.hwdz.com.cn](http://www.hwdz.com.cn)